



3/4 TON: MODEL #8025, 8026 CHILLER:

AUTOMOTIVE GRADE chillers designed to operate 24/7 under the most demanding industrial conditions. These chillers are for inside installation. Outside and split versions are available on request.

- **NOMINAL CAPACITY:** 8,000 BTU/hr (3/4 -ton) @ 90°F ambient
- **CONTROL:** Digital temperature controller
- **PUMP:** 1HP centrifugal, stainless steel with a maximum output of 20gpm @35psi WATER
- **BYPASS:** Internal pressure set, allows low external water usage
- **EVAPORATOR:** Stainless steel brazed plate, external to tank
- **CONDENSER:** Air-cooled, horizontal intake and exhaust
- **FILTERS:** Washable air intake and water return filters provided
- **TANK:** 15-gallon non-metallic
- **WATER MAKEUP:** Automatic, water float valve
- **SAFETY SYSTEM:** Low Water Flow interlock switch
 - Low and High Freon safety system and indicating lights
 - Overload protection for compressor and water pump
- **SERVICE HOT ABILITY:** Can be inspected and serviced while running with all panels removed
- **VOLTAGE:** Model 8025 = 230V, 1Ø, 14A full load
Model 8026 = 115V, 1Ø 29A full load.
- **SIZE:** 46" X 28" X 29" (L X W X H)
- **WEIGHT:** Approximately 425 lbs.